



AM200 *EVOLUTION*

AMPLIFIER.

Improved audio performance, new speaker terminals...

- 8 mm brushed, micro-blasted and anodized aluminum front panel, high-precision engraving.
- 1.5 mm steel chassis.
- Two 340 VA toroidal transformers.
- High-quality and shielded MKP link capacitors.
- Bipolar transistor and LED current sources to ensure perfect voltage stability.
- Specific printed circuit with nickel/gold finish.
- New tellurium copper speaker outputs.
- 12V Trigger input.



AM200 EVO

TECHNICAL DATA

| | |
|------------------------------|----------------|
| Power Wrms/channel/8Ω: | 120 W |
| Power Wrms/channel/4Ω: | 200 W |
| Pulse power/channel: | 300 W |
| Power supply: | 2×340 VA |
| Total of capacitors: | 59 420 μF |
| Number of inputs: | 1 RCA |
| Consumption with switch off: | 0 W |
| Consumption in operation: | 20 W - 600 W |
| Input impedance: | 220 kΩ |
| Sensitivity: | 1,77 V |
| Signal/noise ratio: | 100 dB |
| Distortion at 1 kHz: | 0,05% |
| Bandwidth: | 5 Hz - 200 kHz |
| Rise time: | 1,5 μs |
| Dimensions: | 440×295×95 mm |
| Weight: | 12 kg |

ATOLL
ELECTRONIQUE

High Fidelity Material
designed and manufactured in France

MADE IN FRANCE